



Declaration of Performance according to EU BauPVO 305/2011

1 DoP Reference number	ST/G1/5026		
2 Product description	Separator for light liquids Oleopator-C-FST-HPC-LLT		
3 Product specification: (Numbers or Specification of product)	Oleopator-C-FST-HPC-LLT NS (x) / ST (y) (see following page)		
4 Intended use	Light liquid removal from wastewater to protect drainage systems and surface water		
5 Manufacturer	ACO Beton GmbH Mittelriedstraße 25 D-68642 Bürstadt		
6 Authorised representative	Irrelevant		
7 Assessment and verification of constancy of performance	System 3 and System 4		
8 Relevant harmonised standard	DIN EN 858-1:2005 + DIN EN 858-2:2003 + DIN EN 13501-1:2007		
9 First year of CE marking	2023		
10 Notified body	Irrelevant		
11 Type test report reference number	Irrelevant		
12 Essential characteristics	Main features	DIN EN 858-1	Performance
	Reaction to fire	6.2.8	E
	Fluid resistant	6.3.2	pass
	Effectiveness	4, 6.3.1, 6.3.3 – 6.3.8, 6.5	pass
	Load-bearing capacity	6.4	pass
Durability	6.2	pass	
13 Specific technical documentation (article 37/38)	Installation manual		
14 Other information	–		

The performance of the product according to No. 2 and 3 is conform to the declared performance in No 12.
The manufacturer only is responsible for the creation of this declaration of performance according to No. 5.
Signed for and on behalf of the manufacturer.

Bürstadt, 21.07.2023

Dennis Papadopoulos
Managing Director





Declaration of Performance according to EU BauPVO 305/2011

Information accompanying the CE marking

ACO Beton GmbH Mittelriedstraße 25 68642 Bürstadt 23
DIN EN 858-1:2005 separator systems for light liquids Oleopator-C-FST-HPC-LLT class I with integrated sludge trap Material: concrete Installation parts: PE-HD

Overview of the CE marked separator systems for light liquids Type Oleopator-C-FST-HPC-LLT

NS (x)	ST (y)	Oil storage capacity (l)	Ø D (mm)
3	300	163	1000
3	600	163	1000
3	900	464	1200
6	600	160	1000
6	1200	236	1200
10	1000	273	1200
6-10	2000	576	1500
10	2500	576	1500
10	3000	798	1750
10	5000	1139	2200
15	1500	464	1500
15	3000	552	1750
15	5000	1163	2200
20	2000	594	1500
20	4000	1163	2200





Declaration of Performance according to EU BauPVO 305/2011

NS (x)	SF (y)	Oil storage capacity (l)	Ø D (mm)
20	6000	1163	2200
30	3000	1513	2200
30	6000	1513	2200
40	5000	1350	2200
50	5000	1350	2200

